

# OXIDISING AGENT STORAGE CABINET

This Australian-made storage unit meets the highest standards in oxidising agent storage, as indicated by its safety signage and directions.

- **Heavy-duty.** Double-walled thermal barrier, with an additional undercoat etch applied before the high-gloss

powder coat finish for added protection.


- **Movable.** Underside base skids for ease of moving full or empty by pallet trolley.
- **Safe.** Alloy contact points – no spark risk. Underside safety strapping to prevent cabinet tipping over.

- **Self-closing.** Automated / self-closing and self-locking mechanisms.
- **Adjustable.** Shelf height.
- **Secure.** Key lock door handles and three point latch locking
- **Compliant.** Fully compliant with Australian Standards

15290015



15290016



15290017



15290018



15290019



15290020



MODEL	DESCRIPTION	DIMENSIONS (mm)	CAPACITY (L)	WEIGHT (kg)
15290015	1 door, 1 shelf	External: 800H x 505W x 500D	30	53
15290016	1 door, 2 shelves	External: 1064H x 570W x 560D	60	70
15290017	2 doors, 1 shelf	External: 800H x 1100W x 500D	100	100
15290018	2 doors, 2 shelves	External: 1295H x 1100W x 500D	160	138
15290019	2 doors, 3 Shelves	External: 1825H x 1100W x 500D	250	187
15290020	2 doors, 3 Shelves	External: 1925H x 1400W x 500D	350	222